

Gancho de seguridad para cadena con pestillo automatico tipo CLC - grado 100

	mm	inch	CMU t 4:1	A mm	B mm	E mm	F mm	H mm	S mm	Kg
A 601 XVK	7/8	5/16	2,50	46	38	111	87	26	18	0,75
A 602 XVK	10	3/8	4,00	56	44	142	106	33	24	1,50
A 603 XVK	13	1/2	6,70	71	57	173	137	43	34	3,10
A 604 XVK	16	5/8	10,00	88	64	213	170	46	36	5,90
A 605 XVK	18/20	3/4	16,00	100	80	239	197	55	52	7,40
A 606 XVK	22	7/8	19,00	113	95	281	225	64	53	12,5
A 607 XVK	24/26	1	27,00	125	87	319	253	78	52	22,5

**Los modelos
nuevos**

A605 XVK,
A606XVK e
A607 XVK
seran disponibles
en Julio 2005




Gancho de seguridad de ojo con pestillo automatico tipo CLO - grado 100

	mm	inch	CMU t 4:1	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	S mm	Kg
B 507 XV	7/8	5/16	2,50	45	37	14	29	133	88	10	27	19	0,80
B 508 XV	10	3/8	4,00	56	45	15	36	167	106	12	33	25	1,55
B 509 XV	13	1/2	6,70	71	50	21	45	200	138	16	42	33	3,15
B 510 XV	16	5/8	10,00	88	64	28	58	251	172	20	46	35	6,05
B 511 XV	18/20	3/4	16,00	100	80	27	64	274	197	21	55	52	7,60
B 512 XV	22	7/8	19,00	113	95	35	71	314	225	26	64	53	12,60
B 513 XV	24/26	1	27,00	125	87	40	80	371	253	33,5	78	52	23,00


**Los modelos
nuevos**

B511 XV,
B512 XV y
B513 XV
seran disponibles
en Julio 2005




Gancho para cadena con lengüeta de seguridad for jada - grado 100

	mm	inch	CMU t 4:1	A mm	B mm	E mm	H mm	S mm	Kg
CCL 8 XVK	7/8	5/16	2,50	40	29	99	21	20	0,55
CCL 10 XVK	10	3/8	4,00	46	32	120	25	27	1,10
CCL 13 XVK	13	1/2	6,70	52	42	136	35	30	1,90




Gancho de anilla con lengüeta de seguridad for jada - grado 100

	mm	inch	CMU t 4:1	A mm	B mm	C mm	D mm	E mm	G mm	H mm	S mm	Kg
COL 8 XV	7/8	5/16	2,50	40	29	11	27	112	10	21	20	0,55
COL 10 XV	10	3/8	4,00	46	33	13	34	131	13	24	26	1,00
COL 13 XV	13	1/2	6,70	52	40	18	44	152	17	35	30	1,80



Acortador de cadena con "U link"- grado 100

	mm	inch	CMU t 4:1	A mm	B mm	LU mm	Kg
SCU 8 XVK	7/8	5/16	2,50	26	30	107	0,50
SCU 10 XVK	10	3/8	4,00	31	37	133	1,05
SCU 13 XVK	13	1/2	6,70	41	48	167	2,15
SCU 16 XVK	16	5/8	10,00	53	64	213	4,20




Acortador de cadena con "U link" y "seguridad"- grado 100

	mm	inch	CMU t 4:1	A mm	B mm	LU mm	Kg
SCAU 8 XVK	7/8	5/16	2,50	26	30	107	0,60
SCAU 10 XVK	10	3/8	4,00	31	37	133	1,20
SCAU 13 XVK	13	1/2	6,70	41	48	167	2,30
SCAU 16 XVK	16	5/8	10,00	53	64	213	4,40



Acoplamiento tipo omega - grado 100

	Chain mm	Sling mm	CMU t 4:1	A mm	E mm	H mm	S mm	Kg
A 402 XVK	7/8	5/16	2,50	23	36	16	12	0,20
A 403 XVK	10	3/8	4,00	32	41	16	15	0,30
A 404 XVK	13	1/2	6,70	42	53	21	20	0,60
A 405 XVK	16	5/8	10,00	50	65	28	25	1,15



Cadena de elevacion - grado 100

	mm	inch	CMU t 4:1	Pitch Pas	W1 mm	W2 mm	Kg/m
A 102 X	7	1/4	2,00	21	9,10	25,90	1,10
A 103 X	8	5/16	2,50	24	10,90	26,90	1,60
A 104 X	10	3/8	4,00	30	13,00	37,00	2,20
A 105 X	13	1/2	6,70	39	16,90	48,10	3,60
A 106 X	16	5/8	10,00	48	20,80	59,20	5,40
A 100 X	19	3/4	14,00	57	24,70	70,30	8,00
A 108 X	22	7/8	19,00	66	29,50	73,50	12,00
A 109 X	26	1	27,00	78	33,80	96,20	15,00