



Item	Chain (mm)	Std packaging pcs.	Nominal dimensions (mm)							Weight/pc. approx (kg)	WLL (t)
			D	E	F	G	H	O (min.)	R		
SKS 6	6	14	35	13	35	16	20.5	28	160	0.6	1.4
SKS 7-8	7 8	12	43.5	13	35	20	26	34	181	1.1	2.5
SKS 10	10	6	56	16	42	24.5	30	45	218	2.0	4
SKS 13	13	3	69	20	49	34.5	40	51.5	269	4.0	6.7
SKS 16	16	1	80	24	60	35.5	50	60	319	6.8	10

HOOK FEATURES

- Dimensions: according to EN 1677-3
- Working Load Limit (WLL): according to EN 1677-3 +25%
- Temperature of use:

-40 to 200 °C	>200 to 300 °C	>300 to 400 °C	>400 °C
100% of WLL	WLL reduced to 90%	WLL reduced to 75%	use not permitted

- Ratio of WLL to Proof Load to Breaking Force (Safety Factor): 1 : 2.5 : 4
- Surface Finishing: Grey epoxy painted

Weissenfels reserves the right to change product design and dimensions without incurring obligations.

Date of creation 21.05.2008	Prepared	Checked	Approved	Date of revision 21.05.2008
--------------------------------	----------	---------	----------	--------------------------------