



Item	Chain (mm)	Std packaging pcs.	Nominal dimensions (mm)						Weight/pc. approx (kg)	WLL (t)
			D	E	G	H	O	R		
WCL 8	8	20	29	18	10	11.5	18	64	0.3	2.5
WCL 10	10	20	40	21	12.6	12.6	22.5	81	0.5	4
WCL 13	13	12	50	27.5	16.7	19	27.5	104	1.1	6.7
WCL 16	16	10	65	40	21	21	33	112.5	2.0	10
WCL 22	22	3	110	59	27	29	48.5	177.5	6.5	19

LINK FEATURES

- Working Load Limit (WLL): according to EN 1677-1 +25%
- Temperature of use:

-40 to 200 °C	>200 to 300 °C	>300 to 400 °C	>400 °C
100% of WLL	WLL reduced to 90%	WLL reduced to 75%	use not permitted

- Ratio of WLL to Proof Load to Breaking Force (Safety Factor): 1 : 2.5 : 4
- Surface Finishing: Grey epoxy painted

Weissenfels reserves the right to change product design and dimensions without incurring obligations.

Date of creation 21.05.2008	Prepared	Checked	Approved	Date of revision 21.05.2008
--------------------------------	----------	---------	----------	--------------------------------